

DISPLAY RANGE

PRODUCT OVERVIEW	 M2	 C3	 C3i	 C3L	 C3Li	 C7
Screen size	2.3"	3.5"	3.5"	3.5"	3.5"	7"
Resolution	128 x 64	320 x 240	320 x 240	320 x 240	320 x 240	800 x 480
Type	Monochrome	Colour	Colour	Colour	Colour	Colour
Touchscreen	-	-	-	-	-	Resistive
Brightness	-	750 NIT	750 NIT	750 NIT	750 NIT	750 NIT
Keys	4	5	5	5	5	-
Data logger	✓	✓	✓	✓	✓	✓
EMC	Class C	Class C	Class C	Class C	Class C	Class C
Shock protection	Group 1	Group 1	Group 1	Group 1	Group 1	Group 1
Analog inputs	1	7	-	7	-	14
Digital inputs	-	3	-	3	-	4
Replay outputs	1	4	-	4	-	8
CAN ports	1	2	1	2	1	2
USB ports	1 mini	1	1	1	1	2
RS232 ports	-	1	1	1	1	1
RS422/485 ports	-	-	-	-	-	-
Operating Temp	-30°C to +80°C	-40°C to +70°C	-40°C to +70°C	-40°C to +70°C	-40°C to +70°C	-30°C to +80°C
IP Rating	IP67	IP67	IP67	IP67	IP67	IP67

DISPLAY RANGE

**PRODUCT OVERVIEW**



	T5	T5i	T7i	R2s	R3s	R3
Screen size	5"	5"	7"	1.4"	2.8"	3"
Resolution	800 x 480	800 x 480	800 x 480	128 x 128	320 x 240	432 x 432
Type	Colour	Colour	Colour	Colour	Colour	Colour
Touchscreen	PCAP	PCAP	PCAP	PCAP	PCAP	PCAP
Brightness	800 NIT	800 NIT	800 NIT	250 NIT	750 NIT	850 NIT
Keys	-	-	-	-	5	-
Data logger	✓	✓	✓	✓	✓	✓
EMC	Class C	Class C	Class C	Class C	Class C	Class C
Shock protection	Group 1	Group 1	Group 1	Group 1	Group 1	Group 1
Analog inputs	1	-	1	-	-	6
Digital inputs	1	-	1	-	-	5
Replay outputs	1	-	1	-	4	5
CAN ports	2	1	2	1	2	1
USB ports	1 + 1 M12	1	1 + 1 M12	-	1	1
RS232 ports	-	-	-	-	-	-
RS422/485 ports	1	-	1	-	-	1
Operating Temp	-20°C to +70°C	-20°C to +70°C	-30°C to +80°C	-40°C to +80°C	-20°C to +70°C	-20°C to +70°C
IP Rating	IP67	IP67	IP67	IP67	IP67	IP67