



Properties

- Low-cost precision accelerometer with compression ceramics
- Charge output, no external power required
- Wide dynamic range
- Rugged stainless steel housing



Piezo design	Compression design	
Output	Charge	
Charge sensitivity	60	pC/g
Sensitivity tolerance	20	%
Measurement range, pos./neg.	5000 / 1000	g
Destruction limit	5000	g
Capacitance without cable	800	pF
Transverse sensitivity	<10	%
Upper frequency limit (3 dB)	15000	Hz
Upper frequency limit (10 %)	10000	Hz
Upper frequency limit (5 %)	7000	Hz
Resonant frequency	>25	kHz
Resonance amplitude	30	dB
Operating temperature range	-35 - 150	°C
Temperature coefficient of voltage sensitivity	0,07 (°C)	%/K
Temperature transient sensitivity	30	m/s ² /K
Acoustic noise sensitivity	0,1	m/s ² /Pa
Magnetic field sensitivity	10	m/s ² /T
Base strain sensitivity	0,2	m/s ² /μD
Weight without cable	45	g
Case material	Stainless steel	
Connector direction	radial	
Connector	UNF10-32	
Mounting	M5	

Typical Frequency Response



Connection Accessories

- 009-UNF-UNF-1,5
- 009-UNF-BNC-1,5
- 010-UNF-BNC-10
- 017
- 025

Mounting Accessories

- 001
- 005
- 029
- 046
- 030

Delivery version with accessories kit KD37/01

- KD37
- 009-UNF-BNC-1,5
- 002
- 006
- 008

Notice: The standard delivery includes an individual data sheet.
Upon request, we also offer DAkkS-accredited calibration.

Manfred Weber

Metra Mess- und Frequenztechnik in Radebeul e.K.

Meissner Str. 58
D-01445 Radebeul
Tel. +49-(0)351-836 2191

Internet: www.MMF.de
Email: Info@MMF.de
Fax: +49-(0)351-836 2940

10.22

