



## Properties

- Low weight
- With insulated base avoiding ground loop problems
- Rugged stainless steel case
- Particularly low temperature coefficient
- Two sensitivity versions (10 and 100 mV/g)




Piezo design	Shear design	
Output	IEPE	
Voltage sensitivity	10	mV/g
Sensitivity tolerance	5	%
Measurement range, pos./neg.	600	g
Destruction limit	5000	g
Transverse sensitivity	<5	%
Lower frequency limit (3 dB)	0,12	Hz
Upper frequency limit (3 dB)	21000	Hz
Lower frequency limit (10 %)	0,25	Hz
Upper frequency limit (10 %)	20000	Hz
Lower frequency limit (5 %)	0,35	Hz
Upper frequency limit (5 %)	8000	Hz
Resonant frequency	>46	kHz
Resonance amplitude	25	dB
Constant current supply	2 - 20	mA
Bias voltage at 4 mA	12 - 14	V
Output impedance	<130	Ω
Residual noise; wide band; RMS	<2000 (0,5 - 20000 Hz)	μg
Noise density 1 Hz	300	μg/√Hz
Noise density 10 Hz	80	μg/√Hz
Noise density 100 Hz	25	μg/√Hz
Noise density 1000 Hz	10	μg/√Hz
Operating temperature range	-30 - 130	°C
Temperature coefficient of voltage sensitivity	0,06 (<0 °C)	%/K
	±0,02 (0 - 80 °C)	%/K
	>0,06 (>80 °C)	%/K
Temperature transient sensitivity	0,01	m/s²/K
Weight without cable	28.5	g
Case material	Stainless steel	
Connector direction	axial	
Connector	TNC	
Mounting	M5	
Isolated mounting	yes	
Protection grade	IP64	


### Typical Frequency Response



### Temperature Coefficient



### Noise Characteristics



### Connection Accessories

- 010-TNC-BNC-1,5

### Mounting Accessories

- 001
- 029
- 046
- 030

### Delivery version with accessories kit KS74C10/01

- KS74C10
- 010-TNC-BNC-1,5
- 001
- 002

**Notice:** The standard delivery includes an individual data sheet.  
Upon request, we also offer DAkkS-accredited calibration.

Manfred Weber

**Metra Mess- und Frequenztechnik in Radebeul e.K.**

Meissner Str. 58

D-01445 Radebeul

Tel. +49-(0)351-836 2191

Internet: [www.MMF.de](http://www.MMF.de)

Email: [Info@MMF.de](mailto:Info@MMF.de)

Fax: +49-(0)351-836 2940

10.22

